

[illegible]

- | | | |
|-----|---|-------|
| 24. | Drive line guards | <hr/> |
| 25. | Dual electric horns | <hr/> |
| 26. | Gauge package | <hr/> |
| 27. | Tinted windshield | <hr/> |
| 28. | 12,500# GVWR cut-a-way van chassis | <hr/> |
| 29. | Rear wheel ratio 4.10 | <hr/> |
| 30. | Dual rear wheels | <hr/> |
| 31. | Heavy duty alternator 200 amp minimum | <hr/> |
| 32. | Front defroster | <hr/> |
| 33. | Driver's sun visor | <hr/> |
| 34. | Two speed intermittent wipers and washers | <hr/> |
| 35. | Front and rear stabilizer bars | <hr/> |
| 36. | Front driver and co-pilot seats | <hr/> |
| 37. | Seating 15 adult capacity, Freedman high back seats
with seat belts | <hr/> |
| 38. | Cloth upholstery | <hr/> |
| 39. | Aisle side padded rubber flip up arm rest | <hr/> |
| 40. | Full body insulation | <hr/> |
| 41. | Gray rubber floor covering | <hr/> |
| 42. | Gray ribbed rubber step tread | <hr/> |
| 43. | Windows - Black aluminum solid pane with tinted
safety glass | <hr/> |
| 44. | Four (4) interior dome lights, driver dome light with
separate switch | <hr/> |
| 45. | Step well light | <hr/> |
| 46. | Two 4" back up lights | <hr/> |
| 47. | 5/8 plywood flooring under rubber | <hr/> |
| 48. | Defroster fan mounted over windshield | <hr/> |
| 49. | 65,000 BTU rear heater floor mounted | <hr/> |
| 50. | Body electrical circuits protected by breakers | <hr/> |
| 51. | Fiberglass molded front door steps with integrated
fender flares | <hr/> |
| 52. | Rear mud flaps | <hr/> |
| 53. | Driver's 3-point, 4-way seat belt with self-locking
Retractors | <hr/> |
| 54. | Radio, AM/FM with four speakers and fade with
auxiliary port | <hr/> |
| 55. | Body undercoating | <hr/> |
| 56. | First aid kit, Illinois specification | <hr/> |
| 57. | Fire extinguisher, Illinois specification 2 1/2 lb. | <hr/> |
| 58. | Reflector flares | <hr/> |
| 59. | Padded header over entrance door | <hr/> |
| 60. | Electric outward opening entrance door | <hr/> |
| 61. | Rear mirror | <hr/> |

62. Lighted switch panel within easy reach of operator _____
63. White rubber wear plate at entrance door _____
64. Molded rubber wheelhouse covers _____
65. Meet FMVSS body construction _____
66. Exterior color-end stripping per school specs _____
67. Back up alarm _____
68. One Transpec - Econo roof hatch _____
69. Emergency exit windows per FMVSS _____
70. Rear air conditioning - 55,000 BTU minimum
dual compressor _____
71. 70.5" Headroom (exterior height approx. 97") _____
72. Floor plan indicating passenger compartment length,
seating arrangements and spacing to be provided. _____
73. Overhead clearance decal _____
74. Rear storage compartment with door ajar buzzer _____
75. Entrance handrails parallel to step _____
76. Modesty panel behind drive and behind step well _____
77. Miles per year per unit 16,000 _____
78. Walk away (Closed-End) type lease _____
79. Seat spacing to be maximum allowed by DOT _____

Options:

1. Exterior electric entrance door key switch _____

Please state warranty and/or guarantee

Manufacturer & Model _____ (Please submit literature)

Expected delivery date _____